



## After construction cleaning floors 2

SYMBOL	pH
DT-05	1

An organic acid-based cleaner designed to remove dust (cement, plaster dust) after building works, hard water stains or cloudy film, residues of alkaline cleaning products. Ideal for waterproof stone, elastic, resin, laminate floorings, varnished wood, clinker, tile and PVC floors.

### APPLICATION:

- Floor resistant to acidic formulations.

### COMPOSITION:

Organic and inorganic acids to 10%, <5% anionic surfactants, excipients

### USAGE:

- use at a dilution of 1-3% (100-300ml/10l of water).
- Apply the solution to the surface using a mop or cloth, extract as much liquid as possible and wipe dry with a cotton mop or cloth

### THREAD:

Product is not a mixture of hazardous in accordance with applicable regulations.  
(Regulation of the European Parliament and Council Regulation (EC) No 1272/2008).

### SELL-BY DATE:

36 months from date of manufacture. Date of production / series and the expiration date stated on the packaging.

### ADDITIONAL INFORMATION:

Accessible additional information in the card of characteristics of the dangerous chemical preparation.

*Contaminated packaging should be emptied. Empty container rinse with water several times, which use it as preparation. Empty packaging can be stored in containers for plastic packaging or transfer to special company to utilization. Observe the provisions of the Act of 13 June 2013. On packaging and packaging waste (Dz. U. 2013, pos. 888*