


**TECHNICAL DATA SHEET**

# Block paving sealer

SYMBOL	pH
DS-11	7

A concentrated sealer formulated to protect block paving. Suitable for both interior and exterior applications. Protects against moisture and dirt. The impregnated surfaces are easier to clean after building works. Reduces the penetration of water, soot, lubricant oils and other oils into surfaces. Environmental safely product. The product does not contain toxic solvents

**APPLICATION:**

- sett stone, paving

**COMPOSITION:**

It does not contain substances classified as hazardous

**USAGE:**

Dilute with water at a ratio from 1:5 to 1:9. Ensure that the surface is clean, free from oil stains, loose debris, leaves and moss. Apply to the dry surface using a sprayer or a brush, distribute evenly over the surface. After 1 hour apply a second coat. In case of surfaces with high absorbency a third coat can be applied. After applying final coat allow 5–6 hours drying time. Attention: Do not apply to heated surface or in direct sunlight. Renew the protective coating after deep cleaning.

**THREAD:**

Product is not a mixture of hazardous in accordance with applicable regulations.  
(Regulation of the European Parliament and Council Regulation (EC) No 1272/2008).

**SELL-BY DATE:**

36 months from date of manufacture. Date of production / series and the expiration date stated on the packaging.

**ADDITIONAL INFORMATION:**

*Contaminated packaging should be emptied. Empty container rinse with water several times, which use it as preparation. Empty packaging can be stored in containers for plastic packaging or transfer to special company to utilization. Observe the provisions of the Act of 13 June 2013. On packaging and packaging waste (Dz. U. 2013, pos. 888*